SUMMER 2018

Product comparison tables

Network video, audio and access control





Network speakers

Network microphone

Network Audio Bridge

Network audio systems

	AXIS C3003-E	AXIS C2005	AXIS C1004-E
Form factor	Horn	In ceiling	Cabinet
Background music	-	V	√
Voice annoucements	√	√	√
Onboard audio clips	√	√	√
Amplifier (Watt)	7	6	6
Power	PoE	PoE	PoE
Sound pressure (1m@1W in dB)	>121	>95	>96
Frequency response	280 Hz - 12,5 kHz	45 Hz - 20 kHz	60 Hz - 20 kHz
Memory card slot	-	√	√
Built-in mic	√	√	√
IP rating	IP66/IP67	-	IP45
Outdoor ready	√	-	√
Special features	VAPIX, ACAP, SIP	AXIS Audio Player included, VAPIX, ACAP, SIP	AXIS Audio Player included, VAPIX, ACAP, SIP

Memory	1 x 8GB	
Storage	128GB	
Operating system	Microsoft Windows 10 IoT Enterprise	
Power	Max: 65 W 90 to 264 V AC	
Connectors	6x USB 3.1 Gen 1, 1x HDMI™ 1.4, Display Port 1.2, Universal Audio Jack, Ethernet, Line out	
Supported monitors	Max: 65 W 90 to 264 V AC	
Number of supported Axis devices	15000+	
Licences included	300	
Number of zones	1000	
Extra licence pack available	√	
Multisite management	V	
Warranty	3 years, onsite hardware replacement service	

Audio Management

Software
AXIS C7050

	2N SIP Mic	
Microphone type	Paging console	
Configurable buttons	12	
Voice announcements	\checkmark	
Onboard audio clips	\checkmark	
Power	PoE, DC in	
Frequency response	400 Hz – 7.5 kHz (-10 dB), 275 Hz – 12 kHz (-20 dB)	
Memory card slot	-	
Outdoor ready	-	
Special features	VAPIX, SIP	

